



Uncontrolled when printed

SW-PIN-003-PDF V3, published 9.5.24

S9 Appliance

Hardware Specification and Operating Parameters

System Information

Processor	Intel Xeon E-2356G
Clock speed, Cache	3.20 GHz - 12 MB Cache
CPU Cores & Threads	6 cores, 12 threads
Memory	16GB DDR4 3200MHz
1Gb RJ45 ports (copper)	6
Other Interfaces	2 x USB 3.0
Air Flow	Air flow exits through the front bezel
Display	1 x Display Port + VGA
Noise Levels	66db max load / 52db idle
Copper Network Cables inc	4
10Gb SFP+ ports (fibre)	N/A
Rail Kit	Y
Hard Drive SSD	480GB SSD - SATA 2.5" 7mm
Additional Storage HDD	N/A

Power

Power Supply	FSP 250W Flex ATX
Voltage	100-240V
TDP	80W

Peripherals

4 x RJ45 CAT6 3mtr cable
1 x Power cable

Dimensions

Motherboard	ASUS P12R-M microATX Server
Form Factor	Short Rackmount, 1U
Width	424mm (16.69")
Depth	293mm (11.53")
Height	44mm (1.73")
Weight	4.2kg

Contact us

Tel: +44 (0)800 047 8191
 Email: enquiries@smoothwall.com
smoothwall.com

Smoothwall Ltd

Second Floor, 2 Whitehall Quay
 Leeds, LS1 4HR
 United Kingdom

smoothwall[®]
 by Gloria